

TruPulse™ 200

A low-cost professional
laser rangefinder with an
inclinometer & data output

**LASER™
TECHNOLOGY**
Measurably Superior

Specifications:

- Dimensions: 12,7cm x 5cm x 9cm
- Weight: 220g
- Data Communication: Serial, via wired RS232 (standard) or wireless Bluetooth® (optional)
- Power: 3,0 volts DC nominal; (2) AA or (1) CRV3
- Eye Safety: FDA Class 1 (CFR 21)
- Environmental: Water & Dust Resistant, NEMA 3, IP 64
- Temperature: -20°C to +60°C
- Optics: 7X Magnification
(Field-of-view: 100 m @ 1000 m)
- Display: In-scope LCD
- Units: Feet, Yards, Meters, and Degrees
- Monopod/tripod mount (1/4" - 20)

Measurement Range:

- Distance: 0 to 1000 m typical, 2000 m
max to reflective target
- Inclination: +/- 90 degrees

Accuracy:

- Distance: +/- 30 cm
- Inclination: +/- 0,25 degrees

Operating Modes:

- Horizontal or vertical distance
- Flexible height routine
- Target acquisition: Closest, Farthest, Continuous

*All specifications are subject to change without notice.

NEW Laser Technology, Inc. introduces the TruPulse™ 200, the first in a new line of low-cost professional laser rangefinders. This compact and lightweight laser provides "thru-the-lens" viewing, eliminating parallax issues so you know the laser energy is traveling directly along your line of sight. Offering crystal clear optics with the data shown -



right in the heads up display so you don't have to take your eye off the target. The diopter adjustment also provides comfortable viewing for eye/sunglass wearers. Utilizing the 200's integrated tilt sensor, you can measure horizontal or vertical distance and instantly calculate the height of any object with the built-in, 2-shot routine! Data communication is via a wired RS232 serial (standard) or go wireless with the Bluetooth® option. Use the Closest, Farthest or Continuous mode for multiple targets.

sorbus
INTERNATIONAL LIMITED

Brook Lane
Westbury
Wiltshire
BA13 4ES

Tel: 01373 825500
Fax: 01373 859333
E-Mail: sales@sorbus-intl.co.uk
Web: www.sorbus-intl.co.uk